


Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
SB1000zMKII	Bandpass Sub	37~ 103Hz -3dB	99,8dB 1W / 1M	2000W AES/ 4ohm
Components	Kast: Berken multiplex 15mm			Netto inhoud: 277,5/60ltr
	18Sound 18LW1400 1000W/98dB 28-2500Hz			
Highpass 30Hz lowpass 100Hz 8ste order 40Hz/Q=3/G=+1,5dB 70Hz/Q=1/G=+1,5dB				
Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.soundshopschylge.nl / 27-01-2014				



Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
SB1000zMKII	Bandpass Sub	37~ 103Hz -3dB	99,8dB 1W / 1M	2000W AES/ 4ohm
Components	Kast: Berken multiplex 15mm			Netto inhoud: 277,5/60ltr
	18Sound 18LW1400 1000W/98dB 28-2500Hz			
Highpass 30Hz lowpass 100Hz 8ste order 40Hz/Q=3/G=+1,5dB 70Hz/Q=1/G=+1,5dB				
Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.soundshopschylge.nl / 27-01-2014				