



Beyma 15LX60 700W/96dB - poorten 10*10*25cm / 42~351Hz -3dB

Highpass 30Hz – lowpass 300Hz 4de order - EQ 40Hz/Q=2/G=+3,5dB – 90Hz/Q=1/G=-1dB/ – 180Hz/Q=1/G=-0,5dB

Beyma SM115K 500W/96,5dB - poorten 10*10*24cm 43~353Hz -3dB

Highpass 30Hz – lowpass 300Hz 4de order - EQ 45Hz/Q=2/G=+2dB

SL SP-38A 500BS 500W/96dB 35-1100Hz - poorten 10*10*24,3cm / 42~335 -3dB

Highpass 30Hz – lowpass 300Hz 4de order - EQ 45Hz/Q=2/G=+2dB – 100Hz/Q=1/G=-0,5dB/ – 160Hz/Q=1/G=-0,5dB

Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
SW-115a	Bass reflex	42~ 312Hz -3dB	96,5dB 1W / 1M	700W RMS/ 8ohm
Components	Kast: Berken multiplex 18mm			Netto inhoud 95Ltr
	Bass speaker: RCF L15P200AK 700W/96dB			
Highpass 30Hz Lowpass 300Hz 4de order 45Hz/Q=2/G=+2dB 300Hz/Q=2/G=+1dB				
Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.boyzpc.nl / 09-08-2004				