



RCF L18P200N 700W/96dB / 41,5~117Hz -3dB poorten10*10*18 - 8cm

Highpass 30Hz – Lowpass 120Hz EQ 40Hz/Q=2/G=+1dB EQ 55Hz/Q=1/G=-1dB

18Sound LW1400 1000W/96,5dB 41,5~113Hz -3dB10*10*15,5 - 9cm

Highpass 30Hz – Lowpass 120Hz EQ 40Hz/Q=3/G=+1dB EQ 65Hz/Q=2/G=-1dB EQ 120Hz/Q=2/G=+1dB

Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
SW-118b	Band pass	37~110Hz -3dB	97,5dB 1W / 1M	500W RMS/ 8ohm
Components	Kast: Berken multiplex 18mm		Netto inhoud rear 115,5Lts front 57,5lts	
	SL SP-46a-500PA 500W/99dB 30-2500Hz			
Highpass 30Hz – Lowpass 120Hz EQ 40Hz/Q=2/G=+4dB EQ 80Hz/Q=2/G=-1dB EQ 120Hz/Q=2/G=+2dB				
Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.boyzpc.nl / 09-08-2004				