



Coax: BMS 15C362 45Hz-20KHz/500+80W/8ohm 80° conical - baspoort 2x 8,36Ø*11,6cm 55Hz - 21KHz -6dB
 Pasief filter 1200Hz 12/18dB 8ohm + L-pad 97,0dB 1W/1M 600W AES / 8ohm

Coax: P-audio SN15-500CX 55Hz-20KHz/600/8ohm 60° conical - baspoort 2x 8,36Ø*19,4cm 55,0Hz - 21KHz -6dB
 passief filter 1500Hz 12dB/okt + Lpad of Convair CNVX911 X-over 97,3dB 1W/1M 600W AES / 8ohm

Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
15coax	Fullrange vented	68Hz - 21KHz -6dB	100dB 1W/1M	350W AES / 8ohm
Components	Kast: Berken multiplex 15mm			Netto inhoud: 51,5Ltr
	Coax: RCF CX15N251 55Hz-20KHz/300+50W/8ohm 60° conical			
	Crossover 1500Hz 12-18dB/okt 8ohm 500watt			

Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.soundshopschylge.nl / 17-07-2018

passief filter B&C XO-4 of 1200Hz 12/18dB/okt 8ohm + Lpad 60,5Hz - 20KHz -6dB 98,6B 1W/1M

Coax: B&C 15CXN76 40Hz-18KHz/450W/8ohm 80° conical - baspoort 2x 8,36Ø*19,4cm 600W AES / 8ohm