



18Sound 15LW1402 700W/96,5dB 35-1100Hz - poorten10\*10\*30 - 3,5cm / 37-143Hz -3dB

Highpass 30Hz - lowpass 150Hz 4de order - EQ40Hz/Q=2/G=7,5dB - EQ80Hz/Q=1/G=-2dB - EQ150Hz/Q=2/G=3dB

Beyma 15LX60 700W/96dB - poorten10\*10\*37 - 2,5cm / 49-149Hz -3dB

Highpass 30Hz - lowpass 150Hz 4de order

SL 38A-500BS 500W/95dB - poorten10\*10\*36 - 3,5cm / 48-143Hz -3dB

Highpass 30Hz - lowpass 150Hz 4de order

Model	Enclosure Design	Frequency Response	Efficiency	Power / imp.
SW-115b	Band pass	43~ 138Hz -3dB	95,2dB 1W / 1M	700W AES/ 8ohm
Components	Kast: Berken multiplex 18mm			Netto inhoud: 65,5/30,5ltr
	RCF L15P200AK 700W/95dB			
Highpass 30Hz lowpass 150Hz 4de order 45Hz/Q=3/G=2 70Hz/Q=2/G=-0,50dB				
Ontwerp: van den Hoogen's Servicebedrijf / Boi van den Hoogen / www.boyzpc.nl / 09-08-2004				